

TYPE APPROVAL CERTIFICATE

This is to certify:
that the Weathertight hatch

with type designation(s)
N19/34.3705

issued to
Fabryka Sprzetu Okretowego MEBLOR S.A.
CZARNKOW, Poland

is found to comply with
DNV rules for classification – Ships
DNV rules for classification – High speed and light craft

Application:

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

Issued at **Høvik** on **2024-06-06**

This Certificate is valid until **2029-06-05**.

DNV local unit: **Gdansk CMC**

Approval Engineer: **Grzegorz Wolski**

for **DNV**



Digitally Signed By:
Odd Arne Lyngstad
Location: **DNV Høvik, Norway**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

N19/34.3705

Is a hatch fabricated from 6- or 8-mm thick steel main plate. Plate is not reinforced by stiffeners. Edge of hatch is stiffened by gasket rim welded at 90-degree angle to the main plate. Hatch is of single acting type with up to six linked toggles and wheel mounted centrally.

Model 11V1

Light opening (H) [mm]	Light opening (B) [mm]	Leaf cover [mm]	Toggle (T)	Hinge (H)	Gasket Rim [mm]	Pressure for 6 mm plate [kN/m ²]	Pressure for 8 mm plate [kN/m ²]
630	630	6 or 8	4	2	40x8	25	30
630	730	6 or 8	4	2	40x8	25	30
730	630	6 or 8	4	2	40x8	25	30
730	730	6 or 8	4	2	40x8	25	30

Model 2V11

Light opening (H) [mm]	Light opening (B) [mm]	Leaf cover [mm]	Toggle (T)	Hinge (H)	Gasket Rim [mm]	Pressure for 6 mm plate [kN/m ²]	Pressure for 8 mm plate [kN/m ²]
630	830	6 or 8	6	2	40x8	25	30
730	830	6 or 8	6	2	40x8	25	30
830	630	6 or 8	6	2	40x8	25	30
830	730	6 or 8	6	2	40x8	25	30
830	830	6 or 8	6	2	40x8	25	30
730	930	6 or 8	6	2	40x8	25	30
830	930	6 or 8	6	2	40x8	25	30
930	730	6 or 8	6	2	40x8	25	30
930	830	6 or 8	6	2	40x8	25	30
930	930	6 or 8	6	2	40x8	25	30
830	1030	6 or 8	6	2	40x8	25	30
930	1030	6 or 8	6	2	40x8	25	30
1030	830	6 or 8	6	2	40x8	25	30
1030	930	6 or 8	6	2	40x8	25	30
1030	1030	6 or 8	6	2	40x8	25	30

For further details see the drawings listed under Type Approval documentation below.

Application/Limitation

The application is limited to vessels built to DNV rules and for a design pressure as per tables above.

Weather tight appliances are subject to hose and function testing after installation onboard the vessel, witnessed by a DNV surveyor, except in cases where plan approval of the hatch arrangement determines that tests are not required.

Hatches are calculated with respect to water pressure only, any other loading pattern is to be assessed on a case-by-case basis.

Dimensions of the light opening of the hatch can be smaller than shown on the drawings, provided that scantlings, maximum distance between the cleats and fabrication method and material are maintained.

Consideration shall be given if located in highly stressed areas or in areas critical to fatigue from global hull loads.

Hatch is to be mounted on top of coaming.

Type Approval documentation

Drawing no. N19/34.3705 dated 15 Sep 2022 from manufacturer.

Tests carried out

According to DNV rules for classification: Class Programme DNV-CP-0338, September 2023

Marking of product

The product is to be marked with the following info:

- Manufacturer's name or brand
- DNV Type Approval Certificate No. TAS000047X
- The specific type designation:

Periodical assessment

DNV surveyor has the permission to perform Certification Retention Survey at any time during the validity period of this certificate. Periodical assessment will be required after two years (+/- 90 days) and after 3.5 years (+/- 90 days) to verify that the conditions for the approval are complied with. Reference is made to DNV-CP-0338.